

Product Profile

Model number: DCR-SR68

80GB Handycam® Camcorder- Blue

<http://tinyurl.com/ybw657p>



Product Specifications:

Hardware

Assignable Dial : No

Light/Flash : LED Video Light

Manual / Auto Lens Cover : Manual

Media Card slot : Memory Stick PRO Duo™ Media¹

S/S & Zoom button on LCD : Yes

Audio

Recording Format : Dolby® Digital 2ch

Microphone : Built-in Zoom Microphone

Convenience Features

Multiple Language Display : Yes

BRAVIA® Sync™ : No

Inputs and Outputs

Audio/Video Remote Terminal : Video / S Video / Audio

Analog Audio/Video Output(s) : Included (via A/V Remote Terminal)

USB Port(s) : Hi-speed (2.0 compliant)

S-Video Output(s) : Sold separately (via A/V Remote jack)

Video

Format : SD (MPEG2)

Video Signal : NTSC color, EIA standards

General

Imaging Device : 1/8" Advanced HAD™ CCD sensor

Pixel Gross : 680K

Video Actual : 410K pixels (16:9), 340K pixels (4:3)

Video Resolution : 720 x 480 (4:3)

Still Actual : 250K pixels (16:9), 340K pixels (4:3)

Still Picture Resolution : 680K pixels

Recording Media : 80GB Non-Removeable Hard Disk Drive Memory Stick PRO Duo™ Media and SD/SDHC(Class 4) media (Sold Separately)

Recording and Playback Times : Standard Definition: HQ = up to 1220 min., SP = up to 1750 min., LP = up to 3660 min. When using 16GB Memory Stick PRO Duo® Media (sold separately): Standard Definition: HQ = up to 235 min., SP = up to 340 min., LP = up to 715 min.

Service and Warranty Information

Limited Warranty Term : Limited Warranty --- 1 Year Parts; 90 Days Labor

Fry's Electronics 3 year PSC Paid \$69.99 and transferable for \$25 fee

Optics/Lens

Lens Type : Carl Zeiss® Vario-Tessar®

35mm Equivalent : 39 - 2340mm (16:9) , 44 - 2640mm (4:3)

Aperture : F1.8-6.0

Digital Zoom : 2000x

Filter Diameter : 30mm

Focal Distance : 1.8 - 108mm

Focus : Full range Auto / Manual (Touch Panel)

Shutter Speed : Auto (Slow Shutter ON) 1/30 - 1/500; Auto (Slow Shutter OFF) 1/60 - 1/500

Minimum Illumination : 3 lux (Auto Slow Shutter On, 1/30 Shutter Speed)

Optical Zoom : 60x

Resolution : 680K pixel

Software

Supplied Software : PMB Ver. 5.0 Supports Windows XP SP3 (64-bit editions and Starter (Edition) are not supported); Windows Vista SP2 (Starter edition is not supported); Windows7 (All editions are supported); Standard installation is required. Operation is not assured if the above OS has been upgraded or in a multi-boot environment.

Operating System Compatibility : Windows XP SP3 (64-bit editions and Starter (Edition) are not supported); Windows Vista SP2 (Starter edition is not supported); Windows7 (All editions are supported); Standard installation is required. Operation is not assured if the above OS has been upgraded or in a multi-boot environment.

Weights and Measurements

Weight (Approx.) : w/o battery: 9oz (280g), w battery 11oz (320g)

Dimensions (Approx.) : 2 1/4 x 2 5/8 x 4 1/4 inch (56 x 65 x 105mm)

Power

Battery Type : InfoLITHIUM® with AccuPower™ Meter System (NP-FV30)

Power Requirements : 7.2V (battery pack); 8.4V (AC Adaptor)

Power Consumption (in Operation) : 2.0W

Convenience

Face Detection : Yes (Exposure Only)

Image Stabilization : SteadyShot® image stabilization

Low Light Capability : Minimum 3 lux

Quick On : Yes

x.v.Color™ : No

Removable Flash Media Compatibility : Memory Stick PRO Duo™ Media and SD/SDHC(Class 4) media (Sold Separately)

Face Index : Yes

Film Roll Index : Yes

Still Image Mode(s) : JPEG

Hybrid : Yes

Fader Effect(s) : Black, White

Exposure : Yes (Touch Panel)

Scene Mode(s) : Auto, Twilight, Candle, Sunrise & Sunset, Fireworks, Landscape, Portrait, Spotlight, Sports, Beach, Snow

Photo Capture from Movie : Yes

PictBridge Compatible : No

Easy Operation : No

Slide Show Mode : Yes

Direct Copy : Yes

Display

LCD Screen : 22.7" Clear Photo™ LCD³ (230 K) display

In the Box

A/V Connecting Cable

AC adaptor (AC-L200)

Application Software / USB Driver / (CD-ROM)

Rechargeable Battery Pack (NP-FV30)

USB Cable

\$429.95 w/ 3yr Fry's Warranty - \$25 Transfer Fee +Tax